查询THS130供应商

TOSHIBA HALL SENSOR GaAs ION IMPLANTED PLANAR TYPE

THS130

HIGH STABILITY MOTOR CONTROL.

DIGITAL TACHOMETER.

- High Internal Resistance. : $R_d = 2k\Omega$ (Typ.)
- Excellent Temperature Characteristics.
- Wide Operating Temperature Range. (; −55~125°C)
- Excellent Output Voltage Linearity.

Unit in mm



1 (+) −3 (−) (INPUT)
2 (+) −4 (−) (OUTPUT)

JEDEC	—
EIAJ	—
TOSHIBA	10-4B1A

Weight : 0.06g

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RAITING	UNIT
Control Voltage	V_C	6	V
Power Dissipation	P_D	150	mW
Operating Temperature Range	T_{opr}	−55~125	°C
Storage Temperature Range	T_{stg}	−55~150	°C

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Internal Resistance (Input)	R_d	$I_C = 1mA$	1.6	2.0	2.4	kΩ
Residual Voltage Ratio	V_{HO}/V_H	$V_C = 5V$, B = 0 / B = 0.1T	—	—	±10	%
Hall Voltage (Note 1)	V_H	$V_C = 5V$, B = 0.1T	130	150	170	mV
Temperature Coefficient (Note 2)	V_{HT}	$I_C = 1mA$, B = 0.1T, T1 = 25°C T2 = 125°C	—	—	−0.06	%/°C
Linearity (Note 3)	ΔK_H	$V_C = 5V$, B1 = 0.05T, B2 = 0.1T	—	—	2	%
Specific Sensitivity (Note 4)	K*	$V_C = 5V$, B = 0.1T	—	30	—	$\times 10^{-2}$/T
Internal Resistance (Output)	R_{OUT}	$I_C = 0.5mA$	4.2	6.0	7.8	kΩ

Note 1 : $V_H = V_{HM} - V_{HO}$ (V_{HM} is meter indication)

Note 2 : $V_{HT} = \frac{1}{V_{H(T1)}} \cdot \frac{V_{H(T2)} - V_{H(T1)}}{T2 - T1} \times 100\ (\%/°C)$

Note 3 : $\Delta K_H = \frac{K_{H(B2)} - K_{H(B1)}}{1/2\{K_{H(B1)} + K_{H(B2)}\}} \times 100\ (\%)$, $K_H = \frac{V_H}{I_C \cdot B}$

Note 4 : $K^* = V_H/(R_d \times I_C \times B) = K_H/R_d$

V_{HO} : Residual Voltage

K_H : Product Sensitivity

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

V_H – V_C



V_H – B



R_d – Ta



R_{OUT} – Ta



V_H – Ta
(CONSTANT VOLTAGE OPERATION)